

STANDARD 4'-0" SECTION:

- 1. ATTACH TOP RAIL AND MID RAIL TO ONE END POST. HAND TIGHTEN SETSCREWS.
- 2. ATTACH OTHER END POST TO TOP RAIL AND MID RAIL. HAND TIGHTEN SETSCREWS.
- 3. LOCATE RAIL ASSEMBLY AND ANCHOR INTO POSITION. ANCHORS NOT PROVIDED.
- 4. USING A LEVEL, CHECK THAT POST ARE VERTICAL AND RAILS ARE LEVEL.
- 5. TIGHTEN ALL SETSCREWS.

AND MUST NOT BE MADE PUBLIC, NOR COUNTIED, NOR USED, TO THE DISADVANTAGE OF SAID HOLLAENDER MFG. CO. AND IS SUBJECT TO RETURN ON DEMAND.						
COPYRIGHT 2013, HOLLAENDER® MANUFACTURING CO.						

NO.	REVISIONS	DATE	APPROVED	
٥	RELEASED FOR APPROVAL	1-15-13	BW	2
				\leq
				STR

STRUCTURAL ENGINEERING GROUP
10285 WAYNE AVENUE
CINCINNATI, OH 45215-6399
PHONE: (800) 772-8800 FAX: (800) 772-8806
WWW.HOLLAENDER.COM

PROJECT				
STRAIGHT RAIL				
SECTION				
4'-0" c/c POST				
42" HIGH RAIL				

DESCRIPTION MODULAR RAIL SECTION DRAWINGS

CRAMM DY:	GG	APPROVED BY:	BW	1-15	-12
50220				NTS	
Į MILL				7060	-s
ALUM.	PIPE/	'ALUM	FITTING	1	7 1

